

HENDERSON

DESIGN IN MOTION

Automated Door Hardware Systems

For Sliding Doors

Evolve



EVOLVE



At PC Henderson, we're not just transforming the way you think about automated sliding door solutions - we're evolving it.

As specialists in the design and manufacture of sliding and folding door hardware systems, we've created Evolve. It's a brand new range of exceptionally convenient and highly sophisticated automated systems that will help you make the most of our Husky range of sliding door equipment in any domestic or light commercial environment.

The perfect enhancement for any sliding door application

With three systems available - the Evolve 60, Evolve 80 and Evolve 80 Sim Kit - that can deliver automation to pocket, single and double sliding doors weighing up to 80kg. Doors can be of a flush, panelled or glazed construction. Evolve is perfect for a huge range of applications from enhancing a luxury property to providing entrance solutions for those with mobility problems. The system is also complemented by a choice of hardwired and wireless control options.

Key Evolve features:

- **Designed to fit in** - Evolve can be installed seamlessly into any environment - even retrospectively and is automated by a quiet and non-intrusive motor.
- **Easy to use** - All units are supplied with two remote control units (single channel). There are, however, optional extras available for even more convenience. Please see below.
- **Safe to operate** - A low operating voltage and sensitive obstacle detection system means Evolve is safe in any application.
- **Simple to install and maintain** - Each Evolve system is simple to install, commission and program and because they have a long service life, maintenance is easy and hassle-free.
- **Built for safety** - With an innovative decoupling option allowing manual operation of the door in the event of power failures, Evolve systems offer a high level of security, and complete peace of mind.

OPTIONAL EXTRAS

Upgrade your Evolve system with your choice of high quality accessories.



Rocker Switch

Wall-mounted switch for one touch control. Switch and surface frame supplied as separate items.

Order codes:

Switch
Aluminium ES/AF
White ES/WF

Surface Frame
White ES/WB



4 Channel Transmitter

A 4 channel remote control that can be used with more than one unit.

Order code:
RS/4



Radio Motion Detector

Battery operated radio motion sensor for total ease of access. Ideal for occasional to moderate level of use.

Order code:
Aluminium ER/AL



Radar Motion Detector

Hardwired radar motion sensor for trigger instant access up to 4 metres away. Ideal for moderate to high level of use.

Order codes:
Black ER/B
White ER/W
Aluminium ER/S



Soffix and Face Fixed Fascias*

A range of aluminium fascias for the perfect finish. Available in lengths of 1.5m, 1.8m, 2m, 2.5m and 3m lengths.

Order codes:

Soffix Fix **F138E** (Evolve 80)
F138SIM (Evolve 80SIM)
Face Fix **F140E** (Evolve 80)
F140SIM (Evolve 80SIM)

*Not available for the Evolve 60 kit

EVOLVE 60 for pocket doors

WOOD

60kg



With Evolve 60, sliding doors can be completely concealed within the wall cavity, making it ideally suited to applications where space is at a premium, such as toilets, bathrooms and kitchens. The supplied kit comes complete with all hardware and automated components.

HARDWARE KIT

Contents:

- Aluminium Track and Header
- Galvanised Steel Wrapped Studs
- Stud Brackets
- Hangers
- Adjustable Floor Guide
- Clip Stop
- Rubber Buffer
- Single Channel Remote Control Unit (pack of 2)

AUTOMATED KIT

Contents:

- Drive Unit
- Tension Wheel
- Drive Belt
- Clutch
- Power Unit
- Manual Transmitter

DRIVE UNIT SPECIFICATION

Drive Rating:	50W
Operation Voltage:	24V safety-low voltage via external power unit. Protection Class IP55
Maximum Operating Speed:	Approximately 0.3m/sec, variable
Running Performance:	Soft start/stop, which is adjustable
Safety Functions:	Obstacle detection in both directions and can be manually decoupled from clutch base (positioned in top of the door)
Closing Option:	Automated closing (adjustable to timed intervals)

To upgrade your system, please see Optional Extras.

Order Code	Maximum Door Size	Maximum Door Weight
EP3/UK	1981 x 762 x 44mm	60kg
EP4/UK	1981 x 838 x 44mm	60kg
EP5/UK	2040 x 762 x 44mm	60kg
EP6/UK	2040 x 826 x 44mm	60kg
EP7/UK	2040 x 726 x 44mm	60kg
EP10/UK	2315 x 930 x 44mm	60kg

EVOLVE 80 for single doors

WOOD

80kg



Evolve 80 offers a standard 2 metre kit, which can be used for a wide variety of openings and applications. The supplied kit comes complete with all hardware and automated components.

HARDWARE KIT

Contents:

- Aluminium Track
- Hangers
- Floor Guide
- Track Stop
- Track Spacers
- Brackets
- Single Channel Remote Control Unit (pack of 2)

AUTOMATED KIT

Contents:

- Drive Unit
- Tension Wheel
- Drive Belt
- Clutch
- Power Unit
- Manual Transmitter

DRIVE UNIT SPECIFICATION

Drive Rating:	50W
Operation Voltage:	24V safety-low voltage via external power unit. Protection Class IP55
Maximum Operating Speed:	Approximately 0.3m/sec, variable
Running Performance:	Soft start/stop, which is adjustable
Safety Functions:	Obstacle detection in both directions and can be manually decoupled from clutch base (positioned in top of the door)
Closing Option:	Automated closing (adjustable to timed intervals)

To upgrade your system, please see Optional Extras.

Order Code	Maximum Door Size	Maximum Door Weight
E80/20UK	2700 x 1100 x 50mm	80kg

EVOLVE 80 Sim for bi-parting doors

WOOD

40kg
per door



Our Evolve 80 Sim Kit is perfect for automated and synchronised opening of double sliding doors, and is ideal for larger openings, doorways and room divisions. The supplied kit comes complete with all hardware and automated components.

HARDWARE KIT

Contents:

- Aluminium Track
- Hangers
- Floor Guide
- Track Stop
- Track Spacers
- Brackets
- Clip Stop
- Pulley Cable
- Cable Fixing Brackets
- Single Channel Remote Control Unit (pack of 2)

AUTOMATED KIT

Contents:

- Drive Unit
- Tension Wheel
- Drive Belt
- Clutch
- Power Unit
- Manual Transmitter

DRIVE UNIT SPECIFICATION

Drive Rating:	50W
Operation Voltage:	24V safety-low voltage via external power unit. Protection Class IP55
Maximum Operating Speed:	Approximately 0.3m/sec, variable
Running Performance:	Soft start/stop, which is adjustable
Safety Functions:	Obstacle detection in both directions and can be manually decoupled from clutch base (positioned in top of the door)
Closing Option:	Automated closing (adjustable to timed intervals)

To upgrade your system, please see Optional Extras.

Order Code	Maximum Door Size	Maximum Door Weight
ESIM/40UK	2700 x 1100 x 50mm	40kg

HENDERSON

P C Henderson Limited

Durham Road, Bowburn,
County Durham DH6 5NG, UK
www.pchenderson.com

UK Technical Customer Services Team

Telephone: 0191 377 7345
Fax: 0191 377 3116
e-mail: sales@pchenderson.com

Export Department

Telephone: +44 (0) 191 377 7346
Fax: +44 (0) 191 377 0755
e-mail: international@pchenderson.com

P C Henderson (Ireland) Limited

Westlink Industrial Estate, Kylemore Road,
Dublin 10, Ireland
Telephone: +353 (0) 1 643 6816
Fax: +353 (0) 1 626 0455
e-mail: sales@pchenderson.ie

Henderson Nederland BV

Postbus 258, 5530 AG Bladel, Holland
Tel: +31 (0) 497 33 2020
Fax: +31 (0) 497 33 2029
e-mail: sales@henderson.nl
www.henderson.nl

Part of the ASSA ABLOY Group of companies.



Evolve
January 2013



Certificate Number 10845
ISO 9001
ISO 14001

